

## BIOTECH - THE PELLETT HEATING



### PZ 100 RL

The PZ 100 RL is the pellet heating with a great nominal capacity, especially designed for housing estates, enterprises, municipal establishments and hotels. Perfect combustion is ensured via lambda probe and air mass sensors. The heating offers a fully automatic heat exchanger and burner cleaning with a generously dimensioned ash container. The pellets are transported via our proven suction technique from the storage room to the pellet container.

Our system offers a CAN-BUS capable microprocessor control and a remote maintenance via internet with appropriate PC software! Up to 16 regulated heating circuits can be activated.



**Unique!**  
 - Power supply line 230 VAC, 50 Hz  
 - gentle pellets transport by proven suction technique


PZ 100 RL

**Dimensions:**

Boiler height	1852 mm
Total height*	2037 mm
Flow	543,5 mm
Return	1437,5 mm
Flue tube connection	front/top
Boiler width	1495 mm
Total width**	1840 mm
Boiler depth	1210 mm
Total depth***	1590 mm
Capacity	30-99 kW
Flue tube connection	∅ 200 mm
Electric connection	230 VAC / 50 Hz / 16 A

\* incl. induced draught when positioned on top  
 \*\* incl. ash container \*\*\* incl. HE-Motor and flue gas pipe connect.  
 height dimensions w/o adjusting feet

**Biotech**  
 THE PELLETT HEATING



Biotech Energietechnik GmbH • Furtmühlstraße 32 • A-5101 BERGHEIM BEI SALZBURG  
 Phone +43 (0)662 / 45 40 72-0 • Fax: +43 (0)662 / 45 40 72-50 • Contact: office@pelletsworld.com